

OCBP -004 203 / 300dpi 4

M / N OCBP -004A / B

□□□

□□8 MB SDRAM □200 Mhz 32 □RISC □□□□ 4 MB□□

□□□□□□□□

□□127□□□5□□□□□□□□□□

□□25.4□□□1□□□□□□□□□□300□□984□□□□□□□□

□□□□□□□□□□

TSPL-EZ □□□□□ TPLE □ TPLZ □□□□

□□□□	OCBP -004A	OCBP -004B
□□□	8□/□□□203 DPI□	12□/□□□300 DPI□
□□□□	□□□□□□□□	
□□□□□□	127□□□5□□□□/□	101.6□□□4□□□/ s
□□□□□□	108□□□4.25□□	104□□□4.09□□□
□□□□□□	2794□□□110□□□□	1016□□□40□□□
□□□□	□□□□□□□□□□□□□□□□□□	
□□□□	20-112□□□0.78□□-4.4□□□	
□□□□	0.06□0.254□□□2.36□10□□□	
□□□□	10□2,794□□□0.39"□110"□	10□1,016□□□0.39"□40"□
□□□□□□	□□127□□□5□□□□□□□□□□	
□□□□	□□300 m□□67□□□1□□□□□□□□□□□□□□40□□□110□□□1.6□□□4.3□□□	
□□	□□□□	
□□□□	234□□□□□□x194.8□□□□□□x302.5□□□□□□	
□□	3.1□□□6.83□□	
□□□	32 □RISC CPU	
□□	4MB□□□□	
	8MB SDRAM	
	SD□□□□□□□□□□□□□□4 GB	
□□	□ USB2.0 □ RS-232□□□□□□□□ Centronics□□□□□□□□□□□□□□10/100 Mbps□□□□□□□□□□□□□□□□□□802.11 b / g / n□□□□□□□□□□	
□□	□□□□□□□□	
	□□□□AC 100-240V□1A□50-60Hz	
	□□□□DC 24V□2.5A□60W	
□□□□□□□□LED	1□□□□□□1□□□□□□□1□LED□3□□□□□□□□□□□□□□	
□□□	□□□□□□□□□□pos□□□□□	
	□□□□□□	
	□□□□□□□□	
	□□□□□□□□	
□□□□	□□	

Resolution	8 dots per inch
Font	TrueType
Barcode	Code 39, Code 93, Code 128, UCC, Code 128, A, B, C, Codabar, 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN, UPC 2/5, MSI, PLESSEY, POS TNET, POS T, PDF-417, Maxicode, DataMatrix, QR
Image	BMAP, BMP, PCX, 256 colors
Rotation	0°, 90°, 180°, 270°
Printers	TSPL, EPL, ZPL, DPL
Temperature	5 to 40°C (25 to 85°F), -40 to 60°C (10 to 90°F)
Certifications	FCC, CE, CCC, CB
Compliance	RoHS
OS	① Windows, ② CD, ③ USB, ④, ⑤, ⑥ 2x 1.5", ⑦ 2x 2, ⑧, ⑨
Connectivity	10/100 Mbps, RS-232, Centronics
Media	0.06 to 0.19mm (500000); 0.20 to 0.25mm (200000)
Dimensions	214 x 84 x 254 mm, 1 kg, 802.11 b/g/n, RFID

Product show:



OCOM

www.ocom.com