

OCBP -006 2

M / N OCBP -006



1

1. 1
2. 1
3. 1
4. 1
5. 1

2

Resolution	203DPI
Label Size	20-60mm
Print Speed	MAX 127mm/s; MIN 50.8mm/s
Memory	DRAM 4M FLASH 4M
Connectivity	USB
Barcode Support	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13 + 2, EAN13 + 5, EAN8, EAN8 + 2, EAN8 + 5, CODABAR, POS TNET, UPC-A, UPCA + 2, UPCA + 5, UPC-E, UPCE + 2, UPC-E + 5, C POS T, MSI, MSIC, PLESSEY, ITF14, EAN14, Qrcode, DM, PDF417
Label Width	0-8
Label Length	0-90-270-360mm (10); 0-90-270-360mm
Supported Languages	PCX, BMP, FLASH, DRAM
Label Thickness	
Label Width	20-60mm
Label Length	80mm
Label Thickness	25mm
Label Width	
Label Length	DC12V 3A
Label Weight	1.04KG

□□□□	190□D□×135□W□×137□H□mm
□□□□	5~45°C□□□□□□20-80□□□□□□
□□	-40□55°C□≤93□RH□40°C□
□□	



