

4

M / NOCBP -012A / B

- /
- 200 MHz 32 RISC;
- 8 MB SDRAM+ 8 MB
-
- 1275
- 25.41300984
- 203 dpi300dpi
- Bartender
-

	OCBP -012A	OCBP -012B
	8/203 DPI	12/300 DPI
	1275/	101.64 / s
	1044.25	1044.09
	117870	88935
	20-1120.78-4.4	
	0.060.2542.3610	
	1011780.39"70"	108890.39"35"
	1275	
	300 m671401101.64.3	
	299x 235x 198.3	
	2.55	
	32 RISC CPU	
	8MB	
	8MB SDRAM	
	SD4 GB	
	•USB2.0 •RS-232•10/100 Mbps •802.11 b / g / n	
	AC 100-240V1A50-60Hz	
	DC 24V2.5A60W	
LED	11LED3	

□□□	□□□□□□□□pos□□□□
	□□□□□
	□□□□□
	□□□□□
□□□□	□□
□□□□	8□□□□□□□□□
	□□TTF□□□
□□	1D□□□Code 39□Code 93□Code 128UCC□Code 128□□A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□□□MSI□PLESSEY□POS TNET□□□POS T
	□□□□PDF-417□Maxicode□DataMatrix□QR□
□□□	BIMAP□BMP□PCX□□□256□□
□□□□□□□□	0°□90°□180°□270°
□□□□□	TSPL
□□□□	□□□□5□40°C□25□85□□□□
	□□□-40□60°C□10□90□□□□
□□	①Windows□□□□CD□□□②□□□□□□□③USB□□□④□□□□⑤□□□□□□□□⑥□□□□□□□x 2□1.5“□□□□x 2□⑦□□□□x 2□⑧□□□□□⑨□□
□□□□□	□□□□□□□□□□□□□□□□□□0.06□0.19mm□500000□; 0.20□0.25mm□200000□
□□□□	□□□□□□□□□□□ 214□□□8.4□□□□□25.4□□□1□□□□□□□□□□□□□□□□□□□□□□802.11 b / g / n□□□□□□□□□□RFID□□□





OCBP-012













OCBP-012





OCBP-012



□□□□

[OCOM](#)□□□□□□□□□□