

OCBP-012 4

200 MHz 32RISC
8 MB SDRAM+ 8 MB

1275
30098425.41
203 dpi300dpi
Bartender

1.

	OCBP -012A	OCBP -012B
	8/203 DPI	12/300 DPI
	1275/	101.64/ s
	1084.25	1044.09
	117870	88935
	20-1120.78-4.4	
	0.060.2542.3610mil	
	1011780.39"70"	108890.3935
	1275	
	300 m671401101.64.3	
	299x 235x 198.3	
	2.55	
	32RISC CPU	
	8MB	
	8MB SDRAM	
	SD4 GB	
	•USB2.0 •RS-232 •10/100 Mbps • WiFi 802.11 b / g / n	
	AC 100-240V1A50-60Hz	
	DC 24V2.5A60W	
LED	11LED3	

□□□□	8□□□□□□□□□□ □□TTF□□□
□□	□□□□□□Code 39□Code 93□Code 128UCC□Code 128□A□B□C□Codabar□□□□2 □5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□ □□□□□MSI□PLESSEY□POS TNET□□□□□ □□□□□PDF-417□Maxicode□DataMatrix□QR□
□□□	BIMAP□BMP□PCX□□□□256□□
□□□□□□□□	0°□90°□180°□270°
□□□□□	TSPL
□□□□	□□□□□5□40°C□25□85□□□□□ □□□-40□60°C□10□90□□□□□
□□	①Windows□□□□CD□□□□②□□□□□□□③USB□□④□□□□⑤□□□□□□□□□⑥□□□□□□□□x 2□1.5“□□□□□x 2□⑦□□□ □□x 2□⑧□□□□□⑨□□□□
□□□□	□□□□□□□□□□□□□□□□0.06□0.19mm□500000□; 0.20□0.25mm□200000□
□□□□	□□□□□□□□□□ 214□□□8.4□□□□□25.4□□□1□□□□□□□□□□□□□□□□□□□□802.11 b / g / n□□□□□□□ □□□□□RFID□□□





OCBP-012















OCBP-012



□□□□

OCOM□□□□□□□□□□