

OCBP-012

OCBP-012A/B

OCBP

OCBP

200 MHz 32-bit RISC

8 MB SDRAM + 8 MB

OCBP

127 5

300 (984') 25.4 (1")

203 dpi 300 dpi

OCBP B artender

OCBP

OCBP

| | OCBP-012A | OCBP-012B |
|----------|--|------------|
| OCBP | OCBP | |
| OCBP | 32 | |
| OCBP | USB2.0 / RS-232 10/100 Mbps 802.11 b/g/n | |
| OCBP LED | 1 1 1 LED 3 | |
| OCBP | TSPL | |
| OCBP | 100 | |
| OCBP | AC 100V -240V 50-60Hz DC 24V / 2.5 A | |
| OCBP | 8MB Flash Memory/8MB SDRAM/Flash memory Max. 4GB | |
| OCBP | Windows USB, , x 2 1.5" x 2 x 2 | |
| OCBP | Windows/Linux/Mac SDK Windows/Android/iOS | |
| OCBP | CE FCC Rohs CCC | |
| OCBP | OCBP/OCBP | |
| OCBP | 8 (203 DPI) | 12 300 DPI |
| OCBP | 127 5 | 101.6 4 |
| OCBP | 108 4.25 | 10 4 4.09 |
| OCBP | 1178 70 | 889 35 |

| | | |
|----------|--|----------------------------|
| □□□□ | BIMAP□BMP□PCX□□□ 256 □□ | |
| □□ | □□□□□ Code 39□Code 93□Code 128UCC□Code 128 □□□ A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN □ UPC 2 (5)digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11 □□□□□PDF-417□Maxicode□DataMatrix□□□□□Aztec | |
| □□□□ | 8 □□□□□□□□□□Windows □□□□□□□□□□ | |
| □□□□□□□□ | 0° , 90° , 180° , 270° | |
| □□□□ | BIMAP□BMP□PCX□□□ 256 □□ | |
| □□ | | |
| □□□□ | □□□□□□□□□□□□□□□□□□ | |
| □□□□ | 20-112mm (0.78"-4.4") | |
| □□□□ | 0.06 ~ 0.254 mm (2.36 ~ 10 mil) | |
| □□□□ | 10 ~ 1178mm (0.39 " ~ 70 ") | 10 ~ 889mm (0.39 " ~ 35 ") |
| □□□□□ | 127 mm (5") OD□□□□ | |
| □□ □□ | □□300m _ | |
| □□□□ | 110mm | |
| □□□□ | 25.4 □□□1 □□□ | |
| □□□□ | | |
| □□ | 299 □□* 235 □□* 198.3 □□ | |
| □□ | □□□3.0kg □□□4.05kg | |
| □□□ | 430*280*260 □□ | |
| 4□1□□ | 560*440*525mm/17.5kg | |
| □□ | | |
| □□□□□□□ | 0 to 4 5 °C , 10%~80% □□□ | |
| □□□□□□□ | -20 □ 60□□□□ 10%~90% □□□ | |