

OCBP-012 4x6 wifi

OCBP-012A/B

OCBP

OCBP

200 M H z 32 RISC

8 MB SDRAM + 8 MB

OCBP

127 5

300 (984') 25.4 (1")

203 dpi 300 dpi

B artender

OCBP

OCBP

	OCBP-012A	OCBP-012B
	32	
	USB2.0 / RS-232 10/100 Mbps 802.11 b/g/n	
LED	1 1 1 LED 3	
	TSPL	
	100	
	AC 100V -240V 50-60Hz DC 24V / 2.5 A	
	8MB Flash Memory/8MB SDRAM/Flash memoryMax. 4GB	
	Windows USB, , x 2 1.5" x 2 x 2	
	Windows/Linux/Mac SDK Windows/Android/iOS	
	CE FCC Rohs CCC	
	8 (203 DPI)	12 300 DPI
	127 5	101.6 4
	108 4.25	10 4 4.09
	1178 70	889 35

□□□□	BIMAP□BMP□PCX□□□ 256 □□	
□□□□		
□□	□□□□□ Code 39□Code 93□Code 128UCC□Code 128 □□□ A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN □ UPC 2 (5)digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11 □□□□□PDF-417□Maxicode□DataMatrix□□□□□Aztec	
□□□□	8 □□□□□□□□□□Windows □□□□□□□□□□	
□□□□□□□□	0° , 90° , 180° , 270°	
□□□	BIMAP□BMP□PCX□□□ 256 □□	
□□		
□□□□	□□□□□□□□□□□□□□□□□□	
□□□□	20-112mm (0.78"-4.4")	
□□□□	0.06 ~ 0.254 mm (2.36 ~ 10 mil)	
□□□□	10 ~ 1178mm (0.39 " ~ 70 ")	10 ~ 889mm (0.39 " ~ 35 ")
□□□□□	127 mm (5") OD□□□□	
□□ □□	□□300m _	
□□□□	110mm	
□□□□	25.4 □□□1 □□□	
□□□		
□□	299 □□* 235 □□* 198.3 □□	
□□	□□□3.0kg □□□4.05kg	
□□□	430*280*260 □□	
4□1□□	560*440*525mm/17.5kg	
□□		
□□□□□□□□	0 to 4 5 °C , 10%~80% □□□	
□□□□□□□□	-20 □ 60□□□□ 10%~90% □□□	











