

□□□□/□□□□□□□□□□

□m / n□OCBP-012a / b□□

□□□

□□□□/□□□□□□

200 MHz 32□RISC□□□□

8 MB SDRAM□+ 8 MB□□

□□□□□□□□□□

□□127□□□5□□□□□□□□□□

300□□984'□□□□25.4□□□1"□□□□

203 DPI□300dpi□□□□□□□□

□□□□□Bartender Label Edition□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□

□□□□□	OCBP -012A	OCBP -012B
□□□□	8□/ mm□203 dpi□	12□□/ mm□300 dpi□
□□□□□	□□□□□□□□	
□□□□□□□□	127 mm□5□□□/ s	101.6 mm□4□□□/ s
□□□□□□□□	108 mm□4.25"□	104 mm□4.09"□
□□□□□□□□	1178mm□70□□□	889□□□35"□
□□□□□	□□□□□□□□□□□□□□□□□□□□□□	
□□□□□	20-112mm□0.78□□-4.4"□	
□□□□□	0.06□0.254 mm□2.36□10□□□	
□□□□□	10□1178 mm□0.39"□70"□	10□889 mm□0.39"□35"□
□□□□□□	127 mm□5"□OD□□□□□□	
□□□□□□□□	300□□□□□□□□ OD 67 mm□1"□□□□□□□□□40 mm□110 mm□1.6"□4.3"□	
□□	□□□□□	
□□□□□	299 mm□d□x 235 mm□w□x 198.3 mm□h□	
□□	2.55kg.	
□□□□	32□RISC CPU	
□□	8MB□□	
	8MB SDRAM.	
	SD□□□□□□□□□□□□□□□4 GB	
□□	•USB2.0□□□□□ •RS-232□□□□□□□□□□•□□□□□□□□10/100 Mbps□□□□□□□□□□ •□□□□□□□□□□□□802.11 B / G / N□□□□□□□□□□□□	

電源	電源規格 AC 100-240V 1A 50-60Hz DC 24V 2.5A 60W
LED	1個 LED 3pin 5mm 100mA 1.5W
位置	位置調整機能あり 調整範囲あり 調整単位あり 調整精度あり
材質	ABS
重量	8g
色	黒
接続	1D 39 93 128 UCC 128 A B C Codabar 2 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 MSI Plessey POS TNET POS T 2D PDF-417 Maxicode DataMatrix QR
画像	Bimap BMP PCX 256色
角度	0° 90° 180° 270°
通信	TSPL
温度	5 40°C 25 85°C -40 60°C 10 90°C
機能	①Windows CD; ②quick; ③USB; ④; ⑤; ⑥x 2 1.5"x 2; ⑦; ⑧media
精度	0.06 0.19mm 50000; 0.20 0.25mm 20000
規格	OD 214 8.4" 25.4 1" 802.11 B / G / N RFIDModule



OCBP-012





OCBP-012





OCBP-012







OCBP-012





OCBP-012





OCBP-012





OCBP-012

