

OCBP-012 0000000000000000

0000OCBP-012A/B

000

00/000

200 M H z 32 0 RISC 000

8 MB SDRAM + 8 MB 00

0000000000

00 127 0005 0000000000

300 0 (984') 00000 25.4 00 (1'') 00

203 dpi 0 300 dpi 00000

00000B artender000000

000000000000000000000000

00

	OCBP-012A	OCBP-012B
00	000	
000	320000	
00	USB2.0 0000/ RS-232000000 00000010/100 Mbps000000 00000000 00 802.11 b/g/n 00000000	
00000000LED	1 0000001 0000000 1 0 LED03 0000000000000	
0000	00	
00000	TSPL	
00000	100 00	
00	000 AC 100V -240V050-60Hz 0000 DC 24V / 2.5 A	
000	00000000000000000000 0000 000	
00	8MB Flash Memory/8MB SDRAM/Flash memory0000Max. 4GB	
00	Windows0000000000000000 USB0,000,000 0000000000 000 x 201.5" 0000 x 2 0000 x 2000000000	
00	00000Windows/Linux/Mac SDK0Windows/Android/iOS	
0000	CE0FCC0Rohs0CCC 0	
0000	0000/00	
000	8 0/00 (203 DPI)	12 0/000300 DPI0
0000000000	127 0005000/0	101.6 0004000/0
0000000000	108 0004.25 000	10 4 0004.09000
0000000000	117800070000	889 00035000

□□□□	BIMAP□BMP□PCX□□□ 256 □□
□□	□□□□□ Code 39□Code 93□Code 128UCC□Code 128 □□□ A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN □ UPC 2 (5)digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11 □□□□□PDF-417□Maxicode□DataMatrix□□□□□Aztec
□□□□	8 □□□□□□□□□□Windows □□□□□□□□□□
□□□□□□□□	0° , 90° , 180° , 270°
□□□□	BIMAP□BMP□PCX□□□ 256 □□
□□	
□□□□	□□□□□□□□□□□□□□□□□□
□□□□	20-112mm (0.78"-4.4")
□□□□	0.06 ~ 0.254 mm (2.36 ~ 10 mil)
□□□□	10 ~ 1178mm (0.39 " ~ 70 ") 10 ~ 889mm (0.39 " ~ 35 ")
□□□□□	127 mm (5") OD□□□□
□□ □□	□□300m _
□□□□	110mm
□□□□	25.4 □□□1 □□□
□□□□	
□□	299 □□* 235 □□* 198.3 □□
□□	□□□3.0kg □□□4.05kg
□□□	430*280*260 □□
4□1□□	560*440*525mm/17.5kg
□□	
□□□□□□□	0 to 4 5 °C , 10%~80% □□□
□□□□□□□	-20 □ 60□□□□ 10%~90% □□□