

□□□

32-bit CPU
 8MB SDRAM,8MB Flash
 203 dpi □□□
 152mm(6'')/s □□□□□
 108mm □□□□
 25.4-112mm (0.78'-4.56')□□□□□□
 □□TSPL EPL ZPL DPL□□

□□□

□□□□	
□□	OCBP-014B
□□	□□□□□□
□□	USB
□□□	32 □ CPU
□□	8MB □□8MB SDRAM
□□□□□	30□□
□□	□□ AC 100V -240V □ 50-60Hz □□□□ DC 24V / 2.5 A
□□□	□□□□□□□□□□□□□□□□
□□□□	□□ 2 □□
□□□□	□□ 2 □□
□□□□□□□□	0° , 90° , 180° , 270°
□□□□	TSPL EPL ZPL DPL
□□□□	
□□□□	□□□
□□□	203 DPI
□□□□	□□ 152 □□/□
□□□□	□□ 108 □□
□□□□	□□ 1778 □□
□□□□□	
□□	□□□□□ Code 39□Code 93□Code 128UCC□Code 128 □□ A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□ UPC-A□UPC-E□EAN □ UPC 2 □ 5) □□□□□MSI□PLESSEY□POS□□□□ □□POS□ □□□□□ PDF-417□Maxicode□DataMatrix□□□□□
□□	
□□□□	□□□□□□□□□□□ □□□
□□□□	20-116mm
□□□□	0.06-0.20mm
□□□□□	1 01 mm OD□□□□□
□□□□	10-1778mm
□□	
□□	189.62□□ □□□ × 178.5 □□□□□ × 219.03 □□□□□
□□	□□□1.78kg □□□2.38kg
□□□	335*225*235mm
6□1□□	713*350*510mm/15.74kg
□□	
□□□□□□□□	0 to 4 5 °C , 10%~80% □□□
□□□□□□□□	-20 □ 60□□□□ 10%~90% □□□

















**Barcode
Printer**

