

3

OCBP -015



OCBP -015

8

TSPL / ECS / POS

2D

100

2MB DRAM 2MB

25 80

150km

	TSPL / ESC / POS
	203dpi 576
	max = 72mm.
	USB / UR / UL / URL / U + BT / U + WiFi / URL + BT / URL + WiFi
	= 152mm / s = 260mm / s
	20mm-80mm.
	0.06 0.19mm.
DIA	Ø83
	2MB.
	2MB.
	A 12 * 24 B 9 * 17
	GB18030 Big5 24x24dots
/	

PC347PC850PC860PC863PC865WPC1252PC8662pc8522PC858PT1511251		
1D	UPC-A / UPC-E / JAN13EAN13/ JAN8EAN8/ CODE39 / ITF / CODABAR / CODE93 / CODE128 / MSI / ITF-14 / C POS T / PLESSEY	
2D.	QRPDF417DM	
	150.	
	AC 100V-240V 50 / 60Hz	
	DC 24V / 2.5A	
	0°C45°C1080RH	
	-10°C-60°C1090RH	
	CD	
	196d145wx135hmm	
	1.14kg.	
	1.5kg.	
	30x19x18cmlxwxh	1Unit / carton.
	62x36x52cmlxwxh	12/
	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS	
SDK.	AndroidiOS.	



OCBP-015









