OCBP-015 80mm|||wifi||||

||||||OCBP -015

[][TSPL[]ECS / POS[][]

100

 $2MBDRAM \square 2MB \square \square \square \square$

<u>__25</u>_80_____

150km

	nn
	TSPL[]ESC / POS[][][][][]
	203dpi[]576[]/[]
	max = 72mm.
	USB / UR / UL / URL / U + BT / U + WiFi / URL + BT / URL + WiFi
0000	20mm-80mm.
0000	
	0.06[]0.19mm.
	0000 Ø8300
DRAM	2MB.
	2MB.
	□□A□12 * 24□□□□□□B□9 * 17
	GB18030 Big5 24x24dots
00/00	
	PC347\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
1D	UPC-A / UPC-E / JAN13[]EAN13[]/ JAN8[]EAN8[]/ CODE39 / ITF / CODABAR / CODE93 / CODE128 / MSI / ITF-14 / C POS T / PLESSEY[]
2D	QR[]PDF417[]DM
00000	150[[].
	AC 100V-240V 50 / 60Hz
	DC 24V / 2.5A
	0°C[45°C]10[]80[RH
	-10°C-60°C[]10[]90[RH
00	
	196[]d[]x145[]w[]x135[]h[]mm
	1.14kg.
	1.5kg.
	□30x19x18cm□lxwxh□ 1Unit / carton.
	□□62x36x52cm□lxwxh□ 12□/□

	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS
SDK.	Android∏iOS.









