

OCBP-015 80mm wifi

OCBP -015

mm

8mm

TSPL / ECS / POS

2mm

mm

100mm

2MB DRAM 2MB

25 80mm

150km

mm

mm	mm
mm	TSPL / ESC / POS
mm	203dpi 576
mm	max = 72mm.
mm	mm
mm	USB / UR / UL / URL / U + BT / U + WiFi / URL + BT / URL + WiFi
mm	mm = 152mm / s mm = 260mm / s
mm	20mm-80mm.
mm	0.06 0.19mm.
mm	mm Ø83mm
mm	mm
DRAM	2MB.
mm	2MB.
mm	mm A 12 * 24 mm B 9 * 17
mm	GB18030 Big5 24x24dots
mm/mm	mm
mm	PC347 PC850 PC860 PC865 WPC1252 PC866 2 pc852 2 PC858 PT151 1251
1D	UPC-A / UPC-E / JAN13 EAN13 / JAN8 EAN8 / CODE39 / ITF / CODABAR / CODE93 / CODE128 / MSI / ITF-14 / C POS T / PLESSEY
2D	QR PDF417 DM
mm	150mm.
mm	mm
mm	mm
mm	AC 100V-240V 50 / 60Hz
mm	DC 24V / 2.5A
mm	0°C 45°C 10 80 RH
mm	-10°C-60°C 10 90 RH
mm	mm CD
mm	196 d x 145 w x 135 h mm
mm	1.14kg.
mm	1.5kg.
mm	30x19x18cm l x w x h 1Unit / carton.
mm	62x36x52cm l x w x h 12 /

□□	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS
SDK.	Android□iOS.



OCBP-015





OCBP-015





OCBP-015





OCBP-015





OCBP-015

