

OCBP-402DT)

111



□ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□□□□□

DHCP IP

1111

42mm 10W

□□□□□

ROHM50

IOSAndroidHarmonyOSWindowsMAC

|  |                                                                                              |
|--|----------------------------------------------------------------------------------------------|
|  |                                                                                              |
|  | OCBP-402DT                                                                                   |
|  |                                                                                              |
|  | USBUSBUSBWIFIUSBLAN                                                                          |
|  | 32CPU                                                                                        |
|  | 4MB 320KB                                                                                    |
|  | 50                                                                                           |
|  | 100V-240V50-60Hz24V/2.5A                                                                     |
|  | USB                                                                                          |
|  |                                                                                              |
|  | 2                                                                                            |
|  | 2                                                                                            |
|  | 0°90°180°270°                                                                                |
|  | TSPL                                                                                         |
|  |                                                                                              |
|  |                                                                                              |
|  | 203                                                                                          |
|  | 152                                                                                          |
|  | 30-108                                                                                       |
|  | 10-250                                                                                       |
|  |                                                                                              |
|  | 39 93 128UCC 128 A B C Coda bar Interleaved 2 of 5 EAN-8 EAN-13 T PDF417 Maxi Data Matrix QR |
|  | 8 Windows                                                                                    |
|  |                                                                                              |
|  |                                                                                              |
|  | 30-118                                                                                       |
|  | 0.060.22mm                                                                                   |
|  |                                                                                              |
|  | 220*112*102                                                                                  |
|  | 1.02                                                                                         |

|         |                      |
|---------|----------------------|
| □□□     | 248*140*170mm/1.87Kg |
| 8□1□□   | 516*300*360mm/12.4kg |
| □□      |                      |
| □□□□□□□ | 0□45℃□10%□80% □□□    |
| □□□□□□□ | -20□60□□□□10%~90%□□□ |

**THERMAL SHIPPING  
LABEL PRINTER**

**OEM/ODM**

**COMPLETE QUALIFICATION  
SUPPORT CUSTOMIZATION**



# Thermal label printer

Works Perfectly for 4x6 Labels



**OCBP-402DT**

**Media type:** Roll label/fanfold

Printing width: 30-108mm

Printing speed: 50-152mm/s

## Both stacked and rolled labels can be printed



Print roll label



Print stacked labels

# Durable & Cost Saving

1. Thermal Label Printer applies newest direct thermal printing technology.
2. About 1 second to print one 4"x6" shipping label.
3. Save time and money in your shipping and storage.





# Multi-System Compatible

Label Printer can smoothly run on Windows XP, 7, 8,10, Mac OS.  
Please choose Bluetooth version and download Soonmark APP  
to print labels through your smart phones.



Windows 10



Windows 8



Windows 7



Windows XP



Mac OS



(Note: NOT compatible with Chrome OS).

# Multi-Size Compatible

*This printer provides adjustable paper guide rail  
for small companies, enable them to print various sizes of labels  
with width range from **20-118mm***



**Media width**

|———— 118mm ———|



# Printer Internal Components



# OCBP-402DT TECH SPECS



## Driver support

Windows XP,7, 8,10,  
Mac OS



## Printing Method

Direct Thermal



## Resolution

203 dpi



## CPU

32-bit RISC CPU



## RAM

8MB



## Flash

4MB



## Printing Speed

50-152 mm/s



## Printing Width

20-108mm



## Printing Length

25-300mm



## Media Type

Folded paper,  
roll paper,  
die-cut label,  
black mark paper



## Media Width

20-118mm



## Media Thickness

60μm-220μm



## Interfaces Default

USB



## Programming Language

TSPL



## Control Panel

One Feed button  
(three colors for  
three different status)



## Power Adapter

Input: AC 100-240V,  
1A,50-60Hz  
Output: DC 24V,2.5A,60W



## Dimension (WHD)

220\*112\*102



## Weight

1.17kg

# Packing List (default)



















□□□□

[OCBP-402DT□□□](#)

[OCBP-402DT□□□□□□-Android](#)

[OCBP-402DT□□□□□□-IOS](#)

[OCBP-402DT □□□□□□ - Mac OS](#)

[OCBP-402DT □□□□□□ - Windows](#)