

4 □□□□□□□□□□
□□□□ OCBP-402DT)

111



□□□□□

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□□□□□

DHCP IP

□□□□

42mm 10W

□□□□□

ROHM50

IOSAndroidHarmonyOSWindowsMAC

	OCBP-402DT
	USBUSBUSBWIFIUSBLAN
	32CPU
	4MB 320KB
	50
	100V-240V50-60Hz24V/2.5A
	USB
	2
	2
	0°90°180°270°
	TSPL
	203
	152
	30-108
	10-250
	39 93 128UCC 128 A B C Coda bar Interleaved 2 of 5 EAN-8 EAN-13 T PDF417 Maxi Data Matrix QR
	8 Windows
	30-118
	0.060.22mm
	220*112*102
	1.02

□□□	248*140*170mm/1.87Kg
8□1□□	516*300*360mm/12.4kg
□□	
□□□□□□□	0□45℃□10%□80% □□□
□□□□□□□	-20□60□□□□10%~90%□□□

**THERMAL SHIPPING
LABEL PRINTER**

OEM/ODM

**COMPLETE QUALIFICATION
SUPPORT CUSTOMIZATION**



Thermal label printer

Works Perfectly for 4x6 Labels



OCBP-402DT

Media type: Roll label/fanfold

Printing width: 30-108mm

Printing speed: 50-152mm/s

Both stacked and rolled labels can be printed



Print roll label



Print stacked labels

1. Thermal Label Printer applies newest direct thermal printing technology.
2. About 1 second to print one 4"x6" shipping label.
3. Save time and money in your shipping and storage.

-
- A white and blue FedEx SmartPost printer is shown from a three-quarter perspective. A shipping label is being printed and is partially unrolled from the front. The label contains the following information: TO: ORIGIN D'NOVA, FROM: CA, POWER RAIL FACILITY CENTER, 445 E. ALBUQUERQUE RD., ARLINGTON HEIGHTS, IL 60004, USA, S/N: FE9A CA, YZ29, 6351 STEELES AVE E, SCARBOROUGH ON M1X 1N5, (CA), and a barcode. The printer has a blue accent on the right side and a small circular light on top.



Multi-System Compatible

Label Printer can smoothly run on Windows XP, 7, 8,10, Mac OS.
Please choose Bluetooth version and download Soonmark APP
to print labels through your smart phones.



Windows 10



Windows 8



Windows 7



Windows XP



Mac OS



(Note: NOT compatible with Chrome OS).

Multi-Size Compatible

*This printer provides adjustable paper guide rail
for small companies, enable them to print various sizes of labels
with width range from **20-118mm***



Media width

|—————| **118mm** |—————|

Printer Internal Components



OCBP-402DT TECH SPECS



Driver support

Windows XP,7, 8,10,
Mac OS



Printing Method

Direct Thermal



Resolution

203 dpi



CPU

32-bit RISC CPU



RAM

8MB



Flash

4MB



Printing Speed

50-152 mm/s



Printing Width

20-108mm



Printing Length

25-300mm



Media Type

Folded paper,
roll paper,
die-cut label,
black mark paper



Media Width

20-118mm



Media Thickness

60μm-220μm



Interfaces Default

USB



Programming Language

TSPL



Control Panel

One Feed button
(three colors for
three different status)



Power Adapter

Input: AC 100-240V,
1A,50-60Hz
Output: DC 24V,2.5A,60W



Dimension (WHD)

220*112*102



Weight

1.17kg

Packing List (default)

















□□□□

[OCBP-402DT□□□](#)

[OCBP-402DT□□□□□□-Android](#)

[OCBP-402DT□□□□□□-IOS](#)

[OCBP-402DT □□□□□□ - Mac OS](#)

[OCBP-402DT □□□□□□ - Windows](#)