



□□

□□	
□□	OCBP-404DT
□□	□□□□
□□□□	USB / USB+□□
□□□□□□	50□□
□□	□□□AC 100V-240V, 50-60Hz, □□□DC 24V/2.5A
□□	□□□□□□C□□□□□□□□□□
□□□	□□□□□□□□□□
□□□□	□□2□□
□□□□	□□2□□
□□□□□□□□□□	0°□90°□180°□270°
□□□□	TSPL
□□□□	
□□□□	□□□
□□□	203 □□□
□□□□	□□ 140 □□/□
□□□□	25-110□□
□□□□□□	25-250□□
□□□□□□	
□□□□□□□□	□□ 39□EAN13□EAN8□CODABAR□□□□ 128□□□ 93□ITF □□□□□□□□□□□□□□□□□□□□
□□	
□□□□	□□□□□□□□□□□□□□□□
□□□□	35-115□□
□□□□	0.06-0.22□□
□□□□□□	□□□□□□
□□	
□□	180□□*79□□*70□□
□□	□□□750□
□□□	210*135*85mm/0.9Kg
12□□1□	440*290*275□□/11.5□□
□□	

□□□□&□□	0□45°C□10%□80% □□□
□□□□□□□□	-20□50□□□□□10%~90%□□□



OCBP-404DT□□