

OCBP -M1002 4

M / N OCBP-M1002



□□□

v TSPL

v OLED

v 30

v 2400mAh

v 90mm / s

v SDK Windows

v

□□□□	□□
□□□	203dpi
□□	□□□40mm MAX□110mm
□□□□□□	104□□
□□□□	90mm /□□□□□
□□	8MB
Flash	4MB
□□	OLED□□□□□
□□	□□□□
□□□□	□□≤50mm
□□	1□□□Micro USB
	□□V4.0□□□V2.0□V2.1□V2.1 + EDR
	2.4G WIFI 802.11 a / b / g□□□□□□
□□□□	7.4V 2400□□

□□	□□	□□
	□□□□	□□
	□□	□□
□□	□□□	□□
□□□□		ASCII□□A□12×24 / ASCII□□B□9×24 / □□□24×24
□□		TSC / CPCL
□□□		50□□
□□□	□□	XP□Win7□Win8□Win10□ios□Android□Linux□Mac OS
□□	□□	□□□□□0°C—45□□□□□□-20°C—70°C
	□□	□□□10□—80□□□□□5□—90□





OCBP-M1002





OCBP-M1002





OCBP-M1002



5. 點

點點點點點點點點點點點點點點點點點點點點點點

6. 點

點點點點點點點點點點European點點點點點點點點點點...點

點點點點133點點/點點1300點點點點點點點點點點點點點點點點點點點點點點500點點點點O2 50點點點點點點點點點點

點點點點點

點點點點OCOM點

點點點點POS點點ID點點點點點點點點點點點點點點點點500點點點點點

1點點點點點點點點點點O2點Star ...

點點1500點點點點133點點/點點

9點OEM / ODM點點

POS點點點點點點點點點點點點1點點點點

點點點點點點

FCC點CE點Soncap點POA點BIS點點點點

12 + 1點點點點

點“點點點點點”

點點點點點點點點點點點點