

1. 產品名稱/型號
 2. 產品型號 (OCBP-T4201/T4301)

3. 產品圖



4. 產品規格
 5. 產品特點
 6. 產品應用
 7. 產品優勢
 8. 產品兼容性
 9. 產品認證
 10. 產品包裝
 11. 產品價格
 12. 產品售後
 13. 產品說明書
 14. 產品圖紙
 15. 產品樣品
 16. 產品測試
 17. 產品培訓
 18. 產品支持
 19. 產品服務
 20. 產品保障

21. 產品

22. 產品	
--------	--

OCBP-T4201	OCBP-T4301
32 CPU	
USB2.0/USBBT/USBBTWIFI/USBLAN	
TSPL	
100	
AC 100V-240V, 50-60Hz, DC 24V/2.5A	
8MB/8MB SDRAM/	
USB x 21.5" x 2" x 2"	
Windows/Mac SDK/Windows/Android/iOS	
CE/FCC/Rohs/CCC	
8 (203 DPI)	12 (300 DPI)

152 10006"/	127 10005"/
104 10004.09	104 10004.09
1178 100070	889 100035
BIMAPBMPPCX256	
Code 39Code 93Code 128UCCCode 128 A B C CodabarInterleaved 2 of 5EAN-8EAN-13EAN-128UPC-AUPC-EEAN UPC 2 (5) POSTNET POSTGS1 11 PDF-417MaxicodeDataMatrixQR Aztec	
8 Windows	
0°90°180°270°	
BIMAPBMPPCX256	

[illegible]

0	45°C	10%	80%	
-20	60	10%~90%		

	-20~60℃10%~90%











