

00/000000000000
 0000 OCBP-T4201/T4301)

000



00/000000
 200 MHz 32 RISC 0000
 8MB SDRAM8MB000
 0000000000
 152 0006"000000000000
 25.4 (1") 000 300 (984) 00000
 203dpi300dpi000000
 0000ROHM0000000000100000
 00000000000000000000000000
 0000 bartender 0000000
 000000000000IOS/Android/Harmony OS/Windows/MAC000000

00

00	
----	--

OCBP-T4201	OCBP-T4301
32 CPU	
USB2.0/USBBT/USBBTWIFI/USBLAN	
TSPL	
100	
AC 100V-240V, 50-60Hz, DC 24V/2.5A	
8MB/8MB SDRAM/	
USB x 21.5" x 2" x 2"	
Windows/Mac SDK/Windows/Android/iOS	
CE/FCC/Rohs/CCC	
8 (203 DPI)	12 (300 DPI)

152 10006"/	127 10005"/
104 10004.09	104 10004.09
1178 100070	889 100035
BIMAPBMPPCX256	
Code 39Code 93Code 128UCCCode 128 A B C CodabarInterleaved 2 of 5EAN-8EAN-13EAN-128UPC-AUPC-EEAN UPC 2 (5) POSTNET POSTGS1 11 PDF-417MaxicodeDataMatrixQR Aztec	
8 Windows	
0°90°180°270°	
BIMAPBMPPCX256	

[illegible]

0	45°C	10%	80%	
-20	60	10%~90%		

	-20~60℃ 10%~90%











