

1. 產品名稱/型號
 2. 產品型號 (OCBP-T4201/T4301)

3. 產品圖



4. 產品規格
 5. 產品特點
 6. 產品應用
 7. 產品包裝
 8. 產品尺寸
 9. 產品重量
 10. 產品顏色
 11. 產品材質
 12. 產品壽命
 13. 產品兼容性
 14. 產品認證
 15. 產品價格
 16. 產品售後
 17. 產品說明書
 18. 產品保修
 19. 產品培訓
 20. 產品諮詢

21. 產品圖



OCBP-T4201	OCBP-T4301
32 CPU	
USB2.0/USBBT/USBBTWIFI/USBLAN	
TSPL	
100	
AC 100V-240V, 50-60Hz, DC 24V/2.5A	
8MB/8MB SDRAM/	
USB x 21.5" x 2" x 2"	
Windows/Mac SDK/Windows/Android/iOS	
CE/FCC/Rohs/CCC	
8 (203 DPI)	12 (300 DPI)

152 0006"/0	127 0005"/0
104 0004.09 000	104 0004.09 000
1178 00070 000	889 00035 000
BIMAP0BMP0PCX00025600	
000000 Code 390Code 930Code 128UCC0Code 128 000 A0B0C0Codabar0Interleaved 2 of 50EAN-80EAN-130EAN-1280UPC-A0UPC-E0EAN 0 UPC 2 (5) 000000 00000000 POS0TNET POST0GS1 000000 11 000000PDF-4170Maxicode0DataMatrix0QR 00Aztec	
8 0000000000Windows 0000000000	
0°090°0180°0270°	
BIMAP0BMP0PCX00025600	

[illegible]

0	45°C	10%	80%	
-20	60	10%~90%		

	-20~60℃10%~90%











