

熱転写/熱昇華対応
OCBP-T4202/T4302)

特徴



仕様/オプション
200 MHz 32 bit RISC プロセッサ
8MB SDRAM 8MBフラッシュ
標準搭載
152 mm 6" 幅対応
25.4 mm (1") 幅 300 dot (984) 解像度
203dpi~300dpi対応
搭載ROHM高精度センサー100μm
高精度センサー搭載
標準 bartender 対応
対応OS: iOS/Android/Harmony OS/Windows/MAC対応

備考

OCBP-T4202	OCBP-T4302
32 CPU	
USB2.0 / USB+BT / USB+BT+WIFI / USB+LAN	
TSPL	
100	
AC 100V-240V, 50-60Hz, DC 24V/2.5A	
8MB/8MB SDRAM/	
USB x 21.5" x 2" x 2"	
Windows/Mac SDK/Windows/Android/iOS	
8/(203 DPI)	12/(300 DPI)
152 6"/	127 5"/

104 0004.09 000	104 0004.09 000
1178 00070 000	889 00035 000
BIMAP BMP PCX 000256 00	
00000 Code 39 Code 93 Code 128UCC Code 128 000 A B C Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN 0 UPC 2 (5) 00000 0000000 POS TNET POST GS1 000000 11 00000 PDF-417 Maxicode DataMatrix QR 00 Aztec	
8 0000000000 Windows 0000000000	
0° 90° 180° 270°	
BIMAP BMP PCX 000256 00	
000000000000000000000000	
20-112 0000.78"-4.4"	

0.06 ~ 0.254 mm (2.36 ~ 10 mil)	
10 ~ 1178 mm (0.39" ~ 70")	10 ~ 889 mm (0.39" ~ 35")
127 mm (5") OD	
300m	
110mm	
25.4 mm 1 mm	
280mm*210mm*170mm	
2.25kg 3.25kg	
370*240*205mm	
4 500*390*430mm/14.5kg	
0~45°C 10%~80% RH	
-20~60°C 10%~90% RH	

Thermal Transfer Label Printer

Versatility Creates Efficiency

- Thermal Direct Labels
- Thermal Transfer Labels
- PET Silver Labels
- Garment Hang Tags
- Wash Care Labels



Dual Printing Mode

Direct Thermal Print / Thermal Transfer Print

Switch at Ease Between Both Modes

Direct Thermal Mode

MODE 1



Direct
Thermal
Labels

No TTR Ribbons Required

Thermal Transfer Mode

MODE 2



Thermal Transfer Labels

PET Silver Labels

Garment Hang Tags

Wash Care Labels

TTR Ribbons Required

Professional and Durable Print Head

High-resolution Printing at Lightning Speeds

203dpi Printing Speed

152^{Max.}mm/s



Ordinary Print Head

Durability

Professional Print Head

Durability

Versatile Sizes Compatible Adjustable Media Guide

Different Sizes Printed by Guide Width Adjusted Flexibly



118mm
Media Width Max.

130mm
Media O.D. Max.

110mm×300m
Ribbon Size Max.

Various Connectivity

Multiple OS Compatible

Running smoothly with
Windows XP, 7, 8, 10, 11 and Mac OS

USB Connectivity

- ✓ Windows PC
- ✓ Mac

Also compatible with Google Chrome OS after installing the plugin in the Google browser.

Bluetooth Connectivity

For Bluetooth Version Only

- ✓ Windows Laptop
- ✓ Android Phone
- ✓ iPhone
- ✗ Mac

WiFi Connectivity

For WiFi Version Only

- ✓ Windows PC
- ✓ Mac
- ✓ Android Phone
- ✓ iPhone

Ethernet Connectivity

For Ethernet Version Only

- ✓ Windows PC
- ✓ Mac

Widely Applicable Supporting Various Labels



Direct Thermal Labels



PET Silver Labels



Garment Hang Tags



Thermal Transfer Labels



Wash Care Labels



Price Tags



Different Resolution for Option

For Different Printing Needs



For Most Printing Needs



For Fine Text Printing Needs

Resolution	203dpi	300dpi
Label Material	Direct Thermal Labels, Thermal Transfer Labels, PET Silver Labels, Synthetic PP Labels, Garment Hang Tags, Wash Care Labels	
TTR Ribbons	Wax Ribbon, Wax-resin Ribbons, Resin Ribbons, Washable Resin Ribbons	
Available Version	USB / Bluetooth / WiFi / Ethernet	
Media Type	Continuous paper, gap paper, folded paper, black mark paper, hole-punched paper	
Printer Dimension	280×220×168mm(L×W×H)	
Print Width	15-104mm	15-108mm
Print Speed	152mm/s	127mm/s

Default Accessories List



①



②



③



④



⑤



⑥



⑦



⑧



⑨

- ① User Guide ② USB Cable ③ Power Adapter ④ Power Cord
- ⑤ Media Shaft & Baffle Plate x 2 ⑥ Ribbon Shaft x 2
- ⑦ Ribbon Rewind Paper Core ⑧ Ribbon Sample Roll
- ⑨ Label Sample Roll













