□□/□□□□□□□□□□□□

□□□□ OCBP-T4202/T4302)

□□□

□□/□□□□□□□
200 MHz 32 □ RISC □□□□
8MB SDRAM8MB□□□
□□□□□□□□□□□□
152 □□□6”□□□□□□□□□□□□□□□□□
25.4 □□ (1”) □□□ 300 □ (984) □□□□□
203dpi□300dpi□□□□□□
□□□□ROHM□□□□□□□□□□□100□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□ bartender □□□□□□□□
□□□□□□□□□□□□□□□□IOS/Android/Harmony OS/Windows/MAC□□□□□□

□□

□ □	

□□	OCBP-T4202	OCBP-T4302
□□	□□	
□□□	32□CPU	
□□□□□	USB2.0□□□□/ USB+BT / USB+BT+WIFI / USB+LAN□□	
□□□□□	□□	
□□□□□□	TSPL	
□□□□□□□	100□□	
□□	□□□AC 100V-240V, 50-60Hz, □□□DC 24V/2.5A	
□□□□	□□□□□□□

□□□□□□□	104 □□□4.09 □□□	104 □□□4.09 □□□
□□□□□□□□	1178 □□□70 □□□	889 □□□35 □□□
□□□□□	BIMAP□BMP□PCX□□□256□□	
□□□□□□□		
□	□□□□□□ Code 39□Code 93□Code 128UCC□Code 128 □□□ A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN □ UPC 2 (5) □□□□□ □□□□□□□□ POS□□TNET POST□GS1 □□□□□□ 11 □□□□□□PDF-417□Maxicode□DataMatrix□QR □□Aztec	
□□□□□	8 □□□□□□□□□□□Windows □□□□□□□□□□	
□□□□□□□□□□	0°□90°□180°□270°	
□□□	BIMAP□BMP□PCX□□□256□□	
□□		
□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□	
□□□□□	20-112□□□0.78”-4.4”□	

□□□□	0.06 ~ 0.254 □□ (2.36 ~ 10 □□)	
□□□□	10 ~ 1178 □□ (0.39” ~ 70”)	10 ~ 889 □□ (0.39” ~ 35”)
□□□□□□	127 □□ (5“) OD□□□□	
□□□□	□□300m	
□□□□	110□□	
□□□□□□	25.4 □□□1 □□□	
□□		
□□	280□□*210□□*170□□	
□□	□□2.25kg □□:3.25kg	
□□□□	370*240*205□□	
4□1□□□	500*390*430mm/14.5kg	
□□		
□□□□&□□	0□45℃□10%□80% □□□	
□□□□□□□□	-20□60□□□□10%~90%□□□	

Thermal Transfer Label Printer

Versatility Creates Efficiency

- Thermal Direct Labels
- Thermal Transfer Labels
- PET Silver Labels
- Garment Hang Tags
- Wash Care Labels

Dual Printing Mode

Direct Thermal Print / Thermal Transfer Print

Switch at Ease Between Both Modes

Direct Thermal Mode

MODE 1

Direct Thermal Labels

No TTR Ribbons Required

Thermal Transfer Mode

MODE 2

Thermal Transfer Labels

PET Silver Labels

Garment Hang Tags

Wash Care Labels

TTR Ribbons Required

Professional and Durable Print Head

High-resolution Printing at Lightning Speeds

203dpi Printing Speed

152 Max. mm/s

Ordinary Print Head — Durability

Professional Print Head — Durability

Versatile Sizes Compatible Adjustable Media Guide

Different Sizes Printed by Guide Width Adjusted Flexibly

Various Connectivity Multiple OS Compatible

Running smoothly with
Windows XP, 7, 8, 10, 11 and Mac OS

USB Connectivity

- Windows PC
- Mac

Also compatible with Google Chrome OS after installing the plugin in the Google browser.

Bluetooth Connectivity

For Bluetooth Version Only

- Windows Laptop
- Android Phone
- iPhone
- Mac

WiFi Connectivity

For WiFi Version Only

- Windows PC
- Mac
- Android Phone
- iPhone

Ethernet Connectivity

For Ethernet Version Only

- Windows PC
- Mac

Widely Applicable

Supporting Various Labels

Direct Thermal Labels

PET Silver Labels

Garment Hang Tags

Thermal Transfer Labels

Wash Care Labels

Price Tags

Different Resolution for Option

For Different Printing Needs

For Most Printing Needs

For Fine Text Printing Needs

Resolution	203dpi	300dpi
Label Material	Direct Thermal Labels, Thermal Transfer Labels, PET Silver Labels, Synthetic PP Labels, Garment Hang Tags,Wash Care Labels	
TTR Ribbons	Wax Ribbon, Wax-resin Ribbons, Resin Ribbons, Washable Resin Ribbons	
Available Version	USB / Bluetooth / WiFi / Ethernet	
Media Type	Continuous paper, gap paper, folded paper, black mark paper, hole-punched paper	
Printer Dimension	280×220×168mm(L×W×H)	
Print Width	15~104mm	15~108mm
Print Speed	152mm/s	127mm/s

Default Accessories List

1

2

3

4

5

6

7

8

9

① User Guide ② USB Cable ③ Power Adapter ④ Power Cord

⑤ Media Shaft & Baffle Plate x 2 ⑥ Ribbon Shaft x 2

⑦ Ribbon Rewind Paper Core ⑧ Ribbon Sample Roll

⑨ Label Sample Roll

Aocom
#1 your side