

# 2015年USB

2008

## 规格

- 规格;
- 规格;
- 规格;
- 规格;
- 4mil;
- 规格;
- SDK / API;
- 规格;
- 规格;

## 规格

规格	规格	LED
规格	规格	规格
规格	规格	规格
规格	规格	LED
规格	规格	CMOS
规格	规格	640 * 480 256
规格	规格	13mil UPC40
规格	规格	50; 20
规格	规格	≥4mil
规格	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, Bookland, EAN, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 5, 5, 2, 5, NW7, 128, UCC / EAN, 128, GS1-128, IBSB, 128, CODE93, 11, USD-8, MSI / Plessey
规格	2D	PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1
规格	规格	39, 5mil, 50, 120, 39, 10MIL, 25, 250, UPC / EAN, 13mil, 20, 320, 7.5mil, 63, 150, PDF417, 6.6mil, 62, 145
规格	规格	±45° @ 0°, ±30° @ 0°, ±45° @ 0°
规格	规格	USB, USB COM
规格	规格	3.3V, 5V DC
规格	规格	2.0, 400
规格	规格	2.5, 450
DC	规格	5.5V 1A
LED	规格	I
EMC	规格	FCC, 15, IEC60825-1, EN55022 B
规格	规格	-20, +60, -4, 144
规格	规格	-30, +70, -22, 158

□□	5□ - 95□□□□□□□□
□□□	1.5□□5.0□□□□□□□□□□
IP□□	IP54
□□□□	□□□□□□□□□□
□□	
□□	156 * 68 * 83□□
□□	195□□□□□□□□
□□□□	48 * 36 * 47CM□20□□□□□□13.5□□□
	48 * 39 * 52CM□30□□□□□□15KG□

□□□□□

