

PDF417 OCBS-2008

;
 ;
 ;
 4mil;
 ;
 SDK / API;
 ;
 ;

;

;	
;	LED
;	
;	
;	LED
;	
;	CMOS
;	640 * 480 256
;	13mil UPC40
;	50:20
;	≥4mil
;	1D UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, EAN, Bookland, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 2, 5, 2, 5, NW7, UCC / EAN 128, GS1-128, ISBT 128, CODE93, 11, USD-8, MSI / Plessey
;	2D PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1
;	39, 5mil, 50, 120, 39, 10MIL, 25, 250, UPC / EAN, 13mil, 20, 320, 7.5mil, 63, 150, PDF417, 6.6mil, 62, 145
;	±45° @ 0° 0° ±30° @ 0° 0° ±45° @ 0° 0°
;	
;	USB, USB COM
;	3.3V, 5V DC
;	2.0, 400
;	2.5, 450
;	DC, 5.5V 1A
;	LED
;	EMC, FCC, 15, IEC60825-1, EN55022 B
;	
;	-20, +60°C, -4, 144
;	-30, +70°C, -22, 158
;	5, -95
;	1.5, 5.0
;	IP54
;	
;	
;	156 * 68 * 83
;	195
;	48 * 36 * 47CM, 20, 13.5
;	48 * 39 * 52CM, 30PCS, 15KG



