

# OCBS-2008 规格书

规格

|      |    |                                                                                                                                                                                                                                                                                                |
|------|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 外观   |    |                                                                                                                                                                                                                                                                                                |
| 颜色   |    | LED                                                                                                                                                                                                                                                                                            |
| BEEP |    |                                                                                                                                                                                                                                                                                                |
| 尺寸   |    |                                                                                                                                                                                                                                                                                                |
| 重量   |    | LED                                                                                                                                                                                                                                                                                            |
| 性能   |    |                                                                                                                                                                                                                                                                                                |
| 接口   |    | CMOS                                                                                                                                                                                                                                                                                           |
| 分辨率  |    | 640 * 480256                                                                                                                                                                                                                                                                                   |
| 扫描速度 |    | 13mil UPC40/                                                                                                                                                                                                                                                                                   |
| 扫描精度 |    | 50;20                                                                                                                                                                                                                                                                                          |
| 扫描距离 |    | ≥4mil                                                                                                                                                                                                                                                                                          |
| 扫描范围 | 1D | UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey |
|      | 2D | PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite                                                                                                                                                                                                              |
| 扫描精度 |    | Code 39(5mil)50mm~120mm<br>Code 39(10mil)25mm~250mm<br>UPC/EAN (13mil)20mm~320mm<br>Data Matrix(7.5mil)63mm~150mm<br>PDF417(6.6mil)62mm~145mm                                                                                                                                                  |
| 扫描角度 |    | Inclination ±45° @0°Roll and 0°Skew<br>Rotation ±30° @0°Pitch and 0°Skew<br>Deflection ±45° @0°Roll and 0°Skew                                                                                                                                                                                 |
| 接口   |    |                                                                                                                                                                                                                                                                                                |
| 接口类型 |    | USBUSB COM                                                                                                                                                                                                                                                                                     |
| 接口电压 |    | 3.3V5V DC                                                                                                                                                                                                                                                                                      |
| 接口电流 |    | 2.0400                                                                                                                                                                                                                                                                                         |
| 接口频率 |    | 2.5450                                                                                                                                                                                                                                                                                         |
| DC输入 |    | 5.5V 1A                                                                                                                                                                                                                                                                                        |
| LED  |    | I                                                                                                                                                                                                                                                                                              |
| EMC  |    | FCC15IEC60825-1EN55022 B                                                                                                                                                                                                                                                                       |
| 环境   |    |                                                                                                                                                                                                                                                                                                |
| 工作温度 |    | -20+ 60-4144                                                                                                                                                                                                                                                                                   |
| 存储温度 |    | -30+ 70-22158                                                                                                                                                                                                                                                                                  |
| 湿度   |    | 5% - 95                                                                                                                                                                                                                                                                                        |
| 冲击   |    | 1.55.0                                                                                                                                                                                                                                                                                         |
| IP   |    | IP54                                                                                                                                                                                                                                                                                           |
| 防护等级 |    |                                                                                                                                                                                                                                                                                                |
| 包装   |    |                                                                                                                                                                                                                                                                                                |
| 包装尺寸 |    | 156 * 68 *83                                                                                                                                                                                                                                                                                   |
| 包装重量 |    | 195                                                                                                                                                                                                                                                                                            |
| 包装规格 |    | 48 * 36 * 47CM2013.5                                                                                                                                                                                                                                                                           |
|      |    | 48 * 39 * 52CM3015KG                                                                                                                                                                                                                                                                           |



