

OCBS-2008 QR

;
 ;
 ;
 4mil;
 ;
 SDK / API;
 ;
 ;

;

;		
;		LED
;		
;		
;		LED
;		
;		CMOS
;		640 * 480256
;		13mil UPC40/
;		50;20
;		≥4mil
;	1D	UPC-AUPC-EUPC-E1EAN-13EAN-8ISBNBookland EANISSN3939 ASCII32Trioptic 3952 55252NW7128UCC / EAN 128GS1-128ISBT 128CODE9311USD-8MSI / Plessey
;	2D	PDF417MicroPDF417QRDataMatrixAztecGS1
;		395mil50120 3910MIL25250 UPC / EAN13mil20320 7.5mil63150 PDF4176.6mil62145
;		±45°@ 0°0° ±30°@ 0°0° ±45°@ 0°0°
;		
;		USBUSB COM
;		3.3V5V DC
;		2.0400
;		2.5450
;		DC5.5V 1A
;		LED CLASS I
;		EMC15IEC60825-1EN55022 B
;		
;		-20+ 60-4144
;		-30+ 70-22158
;		5 - 95
;		1.55.0
;		IP54
;		
;		
;		156 * 68 * 83
;		195
;		48 * 36 * 47CM13.5KG 20
;		48 * 39 * 52CM30PCS15KG



