

# OCBS -2008usb2d

;  
 ;  
 ;  
 4mil;  
 ;  
 SDK / API;  
 ;  
 ;

;

		LED
		LED
		CMOS
		640 * 480,256
		13mil UPC 40cm / s
		50;20
		≥4mil
	1D	UPC-AUPC-EUPC-E1EAN-13EAN-8ISBNBookland EANISSNCode 39Code 39ASCIICode 32Trioptic Code 39Interleaved 2 of 5Industrial 2 of 5Discrete 2 of 5Matrix 2 of 5CodabarNW7Code 128UCC / EAN 128GS1-128ISBT 128Code93Code 11USD-8MSI / Plessey
	2D	PDF417MicroPDF417QR CodeDataMatrixHan Xin CodeAztec CodeGS1 Composite
		395mil50mm~120mm 3910mil25mm~250mm UPC / EAN13mil20mm~320mm 7.5mil63mm~150mm PDF4176.6mil62145
		±45°@ 0°Roll0°Skew ±30°@ 0°0° ±45°@ 0°Roll0°Skew
		USBUSB COM
		3.3v~5v DC
		2.0w400mA
		2.5w450mA
		5.5V 1A
LED CLASS		
EMC		FCC15IEC60825-1EN55022 B
		-20+ 60-414
		-30+ 70-22158
		5 - 95
		1.55.0
IP		IP54
		156 * 68 * 83
		195
		48 * 36 * 47CM2013.5KG
		48 * 39 * 52CM3015KG



