

□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□**2008**□□

00000

```

00000000;
0000000000;
00000000000000000000;
0000000000000000;
4mil0000000000;
00000000000000;
SDK / API00;
000000;
0000000

```

5

□□		
□□		□□LED
□		□□
□		□□
□□□		□□LED□□□
□□□□		
□□□		CMOS
□□□		640 * 480256□□
□□□□□□□□		13mil UPC40□□/□
□□□		□□50□;□□20□
□□		≥4mil
□□□□	1D	UPC-A□UPC-E□UPC-E1□EAN-13□EAN-8□□□□□□□□□□Bookland EAN□□ISSN□39□□39□□ASCII□□□32□Trioptic 39□□5□□2□□□2 5□□□2 5□□□ □2 5□□□□□NW7□□□□128□UCC / EAN 128□GS1-128□□ISBT 128□CODE93□ □□11□USD-8□□MSI / Plessey□
	2D	PDF417□MicroPDF417□QR□□DataMatrix□□□□□□□□Aztec□□GS1□□
□□		39□□5mil□□□50□□□120□□ 39□□10MIL□□25□□□250□□ UPC / EAN□13mil□□20□□□320□□ □□□□□7.5mil□□63□□□150□□ PDF417□6.6mil□□62□145□□
□□□□		□□±45°@ 0°□□□0°□□ □□±30°@ 0°□□□0°□□ □□±45°@ 0°□□□0°□□
□		
□□		USB□USB COM□□□□□□□
□□□□		3.3V□5V DC
□□□□		2.0□□□400□□□
□□□□		2.5□□□450□□□
DC□□□□		□□5.5V 1A
LED□		□
EMC□□		FCC□15□□□IEC60825-1□EN55022 B□
□□□□		
□□□□		-20□□□□+ 60□□□□-4□□□□144□□□□
□□□□		-30□□□□+ 70□□□□-22□□□□158□□□□

重量	5 - 95kg
寸法	1.5m x 5.0m
IP等級	IP54
材質	ステンレス
色	
寸法	156 * 68 * 83mm
寸法	195mm
寸法	48 * 36 * 47cm 20mm 13.5mm
寸法	48 * 39 * 52cm 30mm 15KG

仕様書

