

**2008**  
**2008**

**2008**

;  
;  
;  
;  
4mil;  
;  
SDK / API;  
;  
;

**2008**

		LED
		LED
		CMOS
		640 * 480 256
		13mil UPC40 /
		50; 20
		≥4mil
	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, Bookland, EAN, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 5, 2, 5, NW7, UCC / EAN 128, GS1-128, IBSB 128, CODE93, 11, USD-8, MSI / Plessey
	2D	PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1
		39, 5mil, 50, 120, 39, 10MIL, 25, 250, UPC / EAN, 13mil, 20, 320, 7.5mil, 63, 150, PDF417, 6.6mil, 62, 145
		±45° @ 0°, ±30° @ 0°, ±45° @ 0°
		USB, USB COM
		3.3V, 5V DC
		2.0, 400
		2.5, 450
		5.5V 1A
		LED
		FCC, 15, IEC60825-1, EN55022 B
		-20, +60, -4, 144
		-30, +70, -22, 158

□□	5□ - 95□□□□□□□□
□□□	1.5□□5.0□□□□□□□□□□
IP□□	IP54
□□□□	□□□□□□□□□□
□□	
□□	156 * 68 * 83□□
□□	195□□□□□□□□
□□□□	48 * 36 * 47CM□20□□□□□□13.5□□□
	48 * 39 * 52CM□30□□□□□□15KG□

□□□□□

