

OCBS -2010



M / N OCBS -2010

OCBS

- ñ 1D/2D;
- ñ C;
- ñ 1D/2D;
- ñ C;
- ñ 1D/2D ;
- ñ 1D/2D;
- ñ 1D/2D;

OCBS	
Resolution	640 * 480 256
Light Source	LED 630 nm ± 10 nm
Light Intensity	0 ~ 100,000 LUX
Field of View	SR 4°; 30°
Scanning Speed	25 /
Supported Codes	2D: DataMatrix, Matrix 2 of 5, MaxiCode, MicroPDF417, MSI Code, PDF417, QR code, Standard 2 of 5, Telepen, TLC 39 1D: Pos, Aztec, BPO, Pos, Codabar, Codablock, Code 11, Code 39, Code 93, Code 128 / EAN128, Dutch Pos, EAN.UCC Composite, Interleaved 2 of 5, Japan Pos, Planet, Plessey Code, Postnet, RSS, UPC / EAN
Minimum Bar Height	≥ 5mil
Maximum Angle	360°
Minimum Angle	65°
Maximum Angle	75°
OCBS	

□□	RS232 / USB □□□□□□□□MS□Mac□□□□□
□□	DC 5 V. ± 5□
□□	300□□ □□□□ 40mA□□□□
□□	1.5□
□□	150 G
□□□□	170□□x 100□□x 75□□
□□□□	
□□□□	-20°C□60°C□-4°F□144°F□
□□□□	-30°C□70°C□-22°F□158°F□
□□	5□ - 95□□□□□□
□□	□□ □1□□2□□□□□0□□ Floor