

000

00000000;
0000000000;
00000000000000000000;
0000000000000000;
05mil00000000000000000000000000;
0000000000000000;
000000;

000

0000	
0000	640 * 480 256000
00	LED 630±10000
00	010LUX
0000	0000SR00004 °;00030 °
0000	2500/00
00	2D DataMatrix00050MAXICODE0MicroPDF4170MSI00PDF4170QR00002 50Telepen0TLC 390000002
00	1D 0000000000000000BPO000000000000Codablock01100390093001280/ EAN1280 00000EAN.UCC000002 500000000000Plessey000Postnet00RSS0UPC / EAN00
00	≥5mil 000000000000
00	360°
00	65°
00	75°
0000	
00	RS232 / USB 0000000000MS0Mac000000
00	DC 5 V ± 50
00	3000 0000 40MA00000
00	1.50
00	150 G
0000	170000`x 100000`x 7500
0000	
0000	-20°C060°C-4°F0144°F0
0000	-30°C070°C-22°F0158°F0
00	50 - 950000000
00	00 01200000000 Floor

OCBS-2010 2D USB



OCBS-2010



www.ocominc.com





OCBS-2010



www.ocominc.com

CE FC





OCBS-2010



www.ocominc.com



OCBS-2010 2D USB



ocom
all your code

OCBS-T009



www.ocominc.com

CE FC

A \$

Detailed description: A black, dome-shaped barcode scanner with a red sensor window and a small display on the front. It sits on a black base.

ocom
all your code

OCBS-T201



www.ocominc.com

CE FC

A \$

Detailed description: A black, upright barcode scanner with a large orange display screen on the front and a sensor window above it. It sits on a black base.

ocom
all your code

OCBS-W230



www.ocominc.com

CE FC

A \$

Detailed description: A handheld barcode scanner with a yellow and black body. It has a yellow trigger and a black sensor window.

ocom
all your code

OCBS-W700



www.ocominc.com

CE FC

A \$

Detailed description: A handheld barcode scanner with a white and black body. It has a yellow trigger and a black sensor window.

ocom
all your code

OCBS-2008



www.ocominc.com

CE FC

A \$

Detailed description: A handheld barcode scanner with a black body and a blue trigger. It has a black sensor window.

ocom
all your code



www.ocominc.com

CE FC

Detailed description: A handheld barcode scanner with a black body and a black trigger. It is connected to a black cable that ends in a USB connector.