

□□□□□□□□

□M / N□OCBS-2011□

□□□

- ñ □□□□□□□□;
- ñ □□□□□□□□□□;
- ñ □□□□□□□□1D□2D□□;
- ñ □□□□□□□□□□□□□□□□;
- ñ 5□□□□□□□□□□□□□□□□;
- ñ □□□□□□□□□□;
- ñ □□□□□□;

□□□□

□□□	640 * 480□□256□□□□□
□ □□	LED□630 nm±10nm□
□□	0□ 100,000 LUX
□□ □□	□□ □□SR□□□□45°;□□□30°
□□ □□	25 □□/□
□□	2D DataMatrix□□□ Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR□□Standard 2 5□Telepen□TLC 39□
	1D □□□□ Post□Aztec□BPO□□□□□□□□Codabar□Codablock□Code 11□Code 39□Code 93□ Code 128 / EAN128□□□□□□□□EAN.UCC□□□□□□Interleaved 2 of 5□□□□ Post□Planet□Plessey Code□Postnet□RSS□UPC / EAN□□
□□	≥5mil □□□□□□□□□□
□	360°
□□	65°
□	75°

□□□□

□□	RS232 / USB □□□□□□□□ □□MS□Mac□□□□□□
□□	DC 5 V ±5□
□□	300□□ □□□□40mA□□□□□
□□	1.5□
□□	150□
□□□□	170□□×100□□×75□□

□□□□

□□ □□	-20°C□ □60°C□-4°F□144°F□
□□ □□	-30°C □70°C□-22°F□158°F□
□□	5□ - 95□□□□□□□□
□□	□□□ 120□□□□□□□□□□

□□□□□



OCBS-2011



www.ocominc.com

CE FC

