

OCBS -2012

Feautre

- ñ ;
- ñ ;
- ñ 1D 2D ;
- ñ ;
- ñ mil ;
- ñ ;
- ñ ;

□□□

□□□□	
□□□	640 * 480,256□□
□□	LED□617 nm±10 nm□
□□	0~100,000 LUX
□□□□	□ 360°\□□ ±60°\□ ±65°
□□□□	300scan /□
□□	2D DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR□□Standard 2 of 5□Telepen□TLC 39□□
	1D □□□□Pos□Aztec□BPO□□□□Pos□□Codabar□Codablock□Code 11□Code 39□Code 93□Code 128 / EAN128□Dutch Pos t□EAN.UCC Com pos ite□Interleaved 2 of 5□Japan Pos t□ Planet□Plessey Code□Pos tnet□RSS□UPC / EAN□□
□□	≥5mil □□□□□□□□
□□	360°
□□	65°
□□□□	75°
□□□□	
□□	RS232 / USB/ USB□□COM
□□	DC 5 V±5□
□□	190 mA□□□□□
□□	1.5□
□□	165G
□□□□	170□□x 60 mm x95□□
□□□□	
□□□□	- □°C□ 65°C□
□□□□	- 20°C□70°C
□□	5□ - 95□□□□□□□
□□	□1□□□□□□□□□0□□



OCBS-2012





OCBS-2012





OCBS-2012

