

# OCBS -2012 Arduino 2d

M / N OCBS -2012



## Feautre

;

;

1D 2D;

;

5mil;

;

;

## 

	640 * 480,256
	LED 617 nm ± 10 nm
	0 ~ 100,000 LUX
	360° ± 60° ± 65°

□□□□		300scan / □
□□	2D	DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR□□Standard 2 of 5□Telepen□TLC 39□□
	1D	□□□□Pos□□Aztec□BPO□□□□Pos□□Codabar□Codablock□Code 11□Code 39□Code 93□Code 128 / EAN128□Dutch Pos t□EAN.UCC Com pos ite□ Interleaved 2 of 5□Japan Pos t□ Planet□Plessey Code□Pos tnet□RSS□UPC / EAN□□
□□		≥5mil□□□□□□□□
□□		360°
□□		65°
□□		75°
□□□□		
□□		RS232 / USB / USB□□COM
□□		DC 5 V±5□
□□		190 mA□□□□□
□□		1.5□
□□		165□
□□□□		170□□x 60□□x95□□
□□□□		
□□□□		-5°C□65°C
□□□□		-20°C□70°C
□□		5□ - 95□□□□□□□
□□		□150□□□□□□□□□

□□□□□





### 1. 1. 1. 1.

#### 1.1. 1.1. 1.1.

1.1.1. 1.1.1. 1.1.1.

1.1.2. 1.1.2. 1.1.2.

#### 2. 2. 2. & 2.

2.1. 2.1. 2.1.

2.2. 2.2. 2.2.

2.3. 2.3. 2.3.

2.4. 2.4. 2.4.

#### 3. 3. 3.

3.1. 3.1. 3.1.

3.2. 3.2. 3.2.

3.3. 3.3. 3.3.

3.4. 3.4. 3.4.

3.5. 3.5. 3.5.

#### 4. 4. 4.

4.1. 4.1. 4.1.

4.2. 4.2. 4.2.

4.3. 4.3. 4.3.

#### 5. 5. 5.

5.1. 5.1. 5.1.

#### 6. 6. 6.

6.1. 6.1. 6.1.

133 1300 O2 500 ..... 50

133 1300

OCOM

500 POS

O2 Star .....

1500 133;

9 OEM / ODM

POS

FCC CE Soncap POA BIS

12 + 1

"