

□□□□□□□□□□□□□□

□M / N□OCBS -2012□

□□□

- 1.□□□□□□□□;
- 2.□□□□□□□□□□;
- 3.□□□□1D□2D□□□□□□□□;
- 4.□□□□□□□□□□□□□□□□;
5. 5mil□□□□□□□□□□□□□□□□;
- 6.□□□□□□□□;
- 7.□□□□□□;

□□□

□□□□	
□□□	640 * 480,256□□
□□	LED□617 nm±10 nm□
□□	0~100,000 LUX
□□□□	□ 360°\□□ ±60°\□ ±65°
□□□□	300scan /□
□□	2D DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR□□Standard 2 of 5□Telepen□TLC 39□□
	1D Australian Pos t□Aztec□BPO□Canada Pos t□Codabar□Codablock□Code 11□Code 39□Code 93□Code 128 / EAN128□Dutch Pos t□EAN.UCC Com pos ite□Interleaved 2 of 5□Japan Pos t□Planet□Plessey Code□Pos tnet□RSS□UPC / EAN □□
□□	≥5mil□□□□□□□□□□
□□	360°
□□	65°
□	75°
□□□□	
□□	RS232 / USB/ USB□□COM
□□	DC 5 V±5□
□□	190 mA□□□□
□□	1.5□
□□	165G

□□□□	170□□x 60□□x95□□
□□□□	
□□□□	- □°C□ 65C
□□□□	- 20°C□70°C
□□	5□ - 95□□□□□□
□□	□1□□□□□□□□0□□





OCBS-2012





OCBS-2012





OCBS-2012





OCBS-2012

