

OCBS -2013 USB

OCBS -2013

OCBS

OCBS;
 1MP 1280 * 800;
 OCBS;
 OCBS;
 OCBS;
 4mil OCBS;
 OCBS;
 OCBS ASCII

OCBS

00		
00		00LED
000		00
00		00
000		00LED000000
0000		
000		CMOS
000		1280 * 800, 25600
000000		13mil UPC 40cm / s
0000		00500; 00200
00		≥4mil
0000	1D	UPC-A00UPC-E00UPC-E100EAN-1300EAN-800ISBN00Bookland EAN000ISSN00Code 3900Code 3900ASCII00Code 3200Trioptic Code 3900Interleaved 2 of 500Industrial 2 of 500Discrete of 200Matrix 2 of 500Codabar00NW700Code 12800UCC / EAN 128 00GS1-12800ISBT 12800Code9300Code 1100USD-800MSI / Plessey
	2D	PDF41700MicroPDF41700QR Code00DataMatrix00Han Xin Code00Aztec Code00GS1 Com pos ite
00		0039005mil0050mm~120mm 00390010mil0025mm~250mm UPC / EAN0013mil0020mm~320mm 0000007.5mil0063mm~150mm PDF417006.6mil00620014500
000		00±45°@ 0°Roll00°Skew 00±30°@ 0°0000°00 00±45°@ 0°Roll00°Skew
00		
00		USB00USB00COM0000000000
0000		3.3v~5v DC

電圧	2.0w/400mA
電圧	2.5w/450mA
電圧	5.5V 1A
LED 色	赤
電圧	
電圧	-20V + 60V -4V 144V
電圧	-30V + 70V -22V 158V
電圧	5V - 95V
電圧	1.5V 5.0V
IP	IP54
電圧	電圧





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013

