

OCBS-2013 Android 1D 2D

OCBS -2013



Feautre

;

1MP 1MP 1280 * 800;

;

1D 2D;

;

4mil;

;

ASCII;

	LED
	LED

CMOS	
1280 * 800,256	
13mil UPC 40cm / s	
50;20	
≥4mil	
1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, Bookland EAN, ISSN, Code 39, Code 39, ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Discrete of 2, Matrix 2 of 5, Codabar, NW7, Code 128, UCC / EAN 128, GS1-128, ISBT 128, Code93, Code 11, USD-8, MSI / Plessey
	2D
	39, 5mil, 50mm~120mm 39, 10mil, 25mm~250mm UPC / EAN, 13mil, 20mm~320mm 7.5mil, 63mm~150mm PDF417, 6.6mil, 62, 145
	±45° @ 0° Roll, 0° Skew ±30° @ 0° Roll, 0° Skew ±45° @ 0° Roll, 0° Skew
	USB, USB, COM
	3.3v~5v DC
	2.0w, 400mA
	2.5w, 450mA
	5.5V 1A
LED CLASS	
	-20, +60, -4, 144
	-30, +70, -22, 158
	5 - 95
	1.5, 5.0
IP	IP54

12 + 1

30 DOA DOA

4.

T / T LC Western Union Escrow T / T Western Union Escrow Paypal Escrow Alipay.com Moneybookers Visa MasterCard Maestro Solo Carte Bleue Pos tePay CartaSi 4B Euro 6000

5.

6.

Eruopean ...

133 1300 O2 500 50

OCOM

500 POS

O2 Star

1500 133;

9 OEM / ODM

POS

FCC CE Soncap POA BIS

12 + 1

“ ”