

# Pixel 1D / 2D

OCBS -2013



## Feautre

1. ;
2. 1MP Pixel 1MP 1280 \* 800;
3. ;
4. 1D 2D ;
5. ;
6. 4mil ;
7. ;
8. ASCII

	LED
	LED

CMOS	
CMOS	CMOS
尺寸	1280*800~2560000
分辨率	13mil UPC 40cm / s
速度	50;20
厚度	≥4mil
应用	1D UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, Bookland EAN, ISSN, Code 39, Code 39, ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Discrete of 2, Matrix 2 of 5, Codabar, NW7, Code 128, UCC / EAN 128, GS1-128, IBSB 128, Code93, Code 11, USD-8, MSI / Plessey
	2D PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
规格	39, 5mil, 50mm~120mm 39, 10mil, 25mm~250mm UPC / EAN, 13mil, 20mm~320mm 7.5mil, 63mm~150mm PDF417, 6.6mil, 62, 145
角度	±45° @ 0° Roll, 0° Skew ±30° @ 0°, 0° ±45° @ 0° Roll, 0° Skew
接口	
接口	USB, COM
电压	3.3v~5v DC
功率	2.0w, 400mA
功率	2.5w, 450mA
电压	5.5V 1A
<b>LED CLASS</b>	
性能	
精度	-20, +60, -4, 144
精度	-30, +70, -22, 158
寿命	5 - 95
速度	1.5, 5.0
<b>IP</b>	IP54
认证	







