

1D 2D

OCBS -2013

Feautre

;

1MP 1MP 1280 * 800

1D 2D

;

4mil

;

ASCII

		LED
		LED
		CMOS
		1280 * 800,256
		13mil UPC 40cm / s
		50; 20
		≥4mil
	1D	UPC-A UPC-E UPC-E1 EAN-13 EAN-8 ISBN Bookland EAN ISSN Code 39 Code 39 ASCII Code 32 Trioptic Code 39 Interleaved 2 of 5 Industrial 2 of 5 Discrete of 2 Matrix 2 of 5 Codabar NW7 Code 128 UCC / EAN 128 GS1-128 ISBT 128 Code93 Code 11 USD-8 MSI / Plessey
	2D	PDF417 MicroPDF417 QR Code DataMatrix Han Xin Code Aztec Code GS1 Com pos ite
		39 5mil 50mm~120mm 39 10mil 25mm~250mm UPC / EAN 13mil 20mm~320mm 7.5mil 63mm~150mm PDF417 6.6mil 62 145

±45°@ 0°Roll 0°Skew	±45°@ 0°Roll 0°Skew
±30°@ 0° 0°	±30°@ 0° 0°
±45°@ 0°Roll 0°Skew	±45°@ 0°Roll 0°Skew
USB COM	
3.3v~5v DC	3.3v~5v DC
2.0w 400mA	2.0w 400mA
2.5w 450mA	2.5w 450mA
5.5V 1A	5.5V 1A
LED CLASS	
-20 + 60 -4 144	
-30 + 70 -22 158	
5 - 95	5 - 95
1.5 5.0	1.5 5.0
IP54	IP54





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013

