

OCBS -2013

OCBS -2013

;
 1MP 1280 * 800;
 ;
 ;
 4mil;
 ;
 ASCII

		LED
		LED
		CMOS
		1280 * 800, 256
		13mil UPC 40cm / s
		50; 20
		≥4mil
	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, Bookland EAN, ISSN, Code 39, Code 39, ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Discrete of 2, Matrix 2 of 5, Codabar, NW7, Code 128, UCC / EAN 128, GS1-128, ISBT 128, Code93, Code 11, USD-8, MSI / Plessey
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
		39 5mil 50mm~120mm 39 10mil 25mm~250mm UPC / EAN 13mil 20mm~320mm 7.5mil 63mm~150mm PDF417 6.6mil 62 145
		±45° @ 0° Roll 0° Skew ±30° @ 0° ±45° @ 0° Roll 0° Skew
		USB, USB, COM
		3.3v~5v DC

□□□□	2.0w□400mA□
□□□□	2.5w□450mA□
□□□□□	□□5.5V 1A
LED □□	□□
□□□□	
□□□□	-20□□□□+ 60□□□□-4□□□□144□□□□
□□□□	-30□□□□+ 70□□□□-22□□□□158□□□□
□□	5□ - 95□□□□□□
□□□	1.5□□5.0□□□□□□□□□□
IP□	IP54
□□□□	□□□□□□□□□□





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013





OCBS-2013

