

H P.performance. 1D /2D

OCBS -2016.

feautre

;

;

4;

;

1D2D;

;

	USB; RS232
	LinuxAndroidWindows XP7,8,10Mac
	;;;;
	CMOS
	LED+LED
	32ARM MCU + DSP
	Code3935cm / sec
	4mil.
	1/5
	LED
	20
	ABS + PC.
	DC 5V±5
	375MW; 226MW; 750MW
	289g±5g.
	L * W * H180 * 115 * 85mm
	60 * 45 * 38.5 cm 50 pcs / cartonnw= 14.45kggw= 16.15kg
	+

□□□□	1D	●Code25□□●Code25□□●Code25-Matri
		●Code39-Regular●Code39-Fullascii●Code32
		●Code93-Regular●Code93-Fullascii●Code128
		●EAN / GSL / UCC-128AUTO●CODABAR●MSI
		●EAN / JAN-13●UPC-A●JAN-8●CODE11●UPCE0
	2D.	●Micro QR●□□□□●QR
		●AZTEC●PDF417
□□□□		ROLL360°□□□30°□YAW45°
□□□□		Code39 4.17MIL□15□□□□□6cm - 12cm
		Code128 4.17MIL□16□□□□□7cm - 10cm
		□□□□10.83mil□8□□□□5cm - 16cm
		□□QR 10.83MIL□8□□□□□7cm - 12cm
□□□□		
IP□□		IP52.
□□□□		0□50°C/ 32□122‰
□□□□		0□50°C/ 32□122‰
□□□□		20□□85□□□□□□
□□□□		20□□85□□□□□□
ESD□□		15kV□□□□
□□□		1.5M□□□□□□□□□□









