

□□□□□□/□□□□□□□

□□□□□OCBS-2017)

□□□□□

□□□□□□□□

□□□□□□

400□□□□□□□□

□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□

□□□

□□		USB; USB□□□□□RS232
□□□□		Linux□Android□Windows XP□7□8□10□MAC
□□□		CMOS□□□
□□		□□LED□□□□+□□LED□□□□
□□□		32 □ ARM □□□ + DSP
□□□		≥400□□PCS90%,CODE 39□
□□□		1/5 □□
□□□□		25□□/□
□□□□		□□
□□□□		□□□□□□□□□□□□
□□□□		□□□□□□□□LED□
□□□□□□		≥25%
□□		ABS+PC
□□		□□ 5V ±5%
□□□□		375mW□□□□□226mW□□□□□750mW□□□□
		□□□□□□
□□		289□±5□
□□□□		□*□*□□180*115*85□□□□mm□
□□□□□□		60*45*38.5 cm 50□/□, NW.=14.45kg , GW.=16.15kg
□□		□□□
□□□□	□□	●Code25-Interleaved ●Code25-Standard ●Code25-Matri
		●Code39-Regular ●Code39-FullASCII ●Code32
		●Code93-Regular ●Code93-FullASCII ●Code128
		●EAN/GSL/UCC-128Auto ●Codabar ●MSI
		●EAN/JAN-13 ●UPC-A ●JAN-8 ●UPCE
	□□	● QR ● Data Matrix ● PDF417
□□□□		Roll360°, Pitch30°, Yaw45°
□□□□		Code39 417□□15□□□□4cm - 8cm
		Code128 4.17mil(16 bytes):7cm - 15cm
		□□□□ 1083 □□8 □□□□3cm - 9cm
		Code QR 20mil (8 bytes): 1cm - 19cm

IP	IP42
Temperature	0 ° 50°C / 32 ° 122°F
Humidity	0 ° 50°C / 32 ° 122°F
Relative Humidity	20% ° 85%
Relative Humidity	20% ° 85%
Static Discharge	15KV
Drop Test	1.5m





OCBS-2017





OCBS-2017





OCBS-2017





OCBS-2017

