

□□□

□□□□□□□□
 □□□□□□
 4mil□□□□□□□□□□
 □□□□□□□□□□
 □□□□□□□□□□1D □ 2D □□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□

□□□

□□□	
□□	OCBS-2017
□□	□□□
□□	ABS+PC
□□□	32□ARM□□□+DSP
□□	USB; USB□□COM□RS232
□□□□	□□□□□□□□LED□
□□□□□□	IP42
□□□□	375mW□□□□□226mW□□□□□750mW□□□□
□□	□□ 5V ±5%
□□□□□□	Linux □ Android □ Windows XP □ 7□8□10 □MAC _ _ _ _
□□	
□□□	CMOS
□□	□□LED(□□)+□□LED(□□)
□□□	≥ 4□□□PCS90%,CODE 39 □
□□□	1/5 □□
□□□□	25□□/□
□□□□	□□
□□□□	□□□□□□□□□□□□□□
ESD□□	15KV□□□□
□□□	□□□□□ 1.5m □□□□
□□□□□	≥25%
□□	1D: Code25-Interleaved , Code25-Standard , Code25-Matrix , Code39-Regular , Code39-FullASCII , Code32 , Code93-Regular , Code93-FullASCII , Code128 , EAN/GSL/UCC-128Auto , Codabar , □□, EAN/JAN-13 , UPC-A , JAN-8 , UPCE 2D□PDF417□□□□□□□□□□
□□□□	Code39 4.17mil(15bytes):4cm-8cm Code128 4.17mil(16bytes):7cm-15cm □□□□10.83mil□8□□□□3cm-9cm □□□ 1083□□8□□□□7cm-12cm
□□□□	Roll360°, Pitch30°, Yaw45°
□□	
□□	□□□320g □□□400g
□□□	195*105*80mm
30 □ 1 □	570*430*280mm/7.0kg
□□	
□□□□□□□	0 to 4 5 °C , 10%~80% □□□
□□□□□□□	-20 □ 60□□□ □10%~90% □□□









