

___OCBS-2017)

400

	USB; USBRS232
	Linux[Android[Windows XP[]7[]8[]10[]MAC
	CMOS[[[[]
	32 [] ARM [][] + DSP
	≥400[[PCS90%,CODE 39[]
	1/5 🔲
	25/_
	≥25%
	ABS+PC
	□□ 5V ±5%
	375mW226mW750mW
	289[]±5[]
	* * 180*115*85 mm
	60*45*38.5 cm 50[/[], NW.=14.45kg , GW.=16.15kg
	●Code25-Interleaved ●Code25-Standard ●Code25-Matri
	●EAN/GSL/UCC-128Auto ●Codabar ●MSI
	●EAN/JAN-13 ●UPC-A ●JAN-8 ●UPCE
	● QR ● Data Matrix ● PDF417
	Roll360°, Pitch30°, Yaw45°
	Code39 417001500004cm - 8cm
	Code128 4.17mil(16 bytes):7cm - 15cm
	□□□□ 1083 □□8 □□□□3cm - 9cm
	Code QR 20mil (8 bytes): 1cm - 19cm

IP[[IP42
	0 □ 50°C / 32 □ 122°F
	0 □ 50°C / 32 □ 122°F
	20% [] 85%[[[[[[]]]]]
	20% [] 85%[][][]
	15KV[[[[[]]]
	000001.5m0000









