

OCBS-2017 / 1D Barcode

OCBS-2017)

Content

1. 1D Barcode
2. 1D Barcode
3. 4D Barcode
4. 1D Barcode
5. 1D Barcode
6. 1D Barcode

Table

OCBS-2017	
Model	OCBS-2017
Processor	ABSPC
Memory	32 MB ARM DSP
Ports	USB; USB; RS232
Display	LED
IP Rating	IP42
Power	375mW (max) 226mW (typ) 750mW (peak)
Voltage	5V ±5%
OS	Linux, XP, 7, 8, 10
OCBS-2017	
Material	CMOS
Light	LED
Resolution	≥ 4 mil, PCS90%, CODE 39
Speed	1/5
Accuracy	25%
Temperature	
Humidity	
Shock	15KV
Vibration	1.5m/s²
Drop	≥25%
Barcode	Code25, Code25, Code25, Code39, Code39-FullASCII, Code32, Code93, Code93-FullASCII, Code128, EAN/GSL/UCC-128, EAN, JAN, UPC-A, 1D, 2D:PDF417, QR Code, Data Matrix
Dimensions	Code39 417x15x4cm-8cm Code128 417x16x7cm-15cm 1083x8x3cm-9cm 1083x8x7cm-12cm
Rotation	Roll360°, Pitch30°, Yaw45°
OCBS-2017	
Weight	320g - 400g
Size	195*105*80mm
30x1x1	570*430*280mm/7.0kg
OCBS-2017	
Operating Temp	0 - 45 °C, 10%~80% RH

□□ □□ □□ □□

-20 □ 60 □□□ , 10%~90% □□□

□□□□









