

OCBS-2018 USB

Feautre

1MP

1MP 1280 * 800;

1D

2D

4mil

4mil

4mil

4mil

Interface	USB; RS232	
OS	Linux, Android, Windows XP, 7, 8, 10, MAC	
Resolution	1MP; 1280 * 800; 2MP; 1920 * 1080; 4MP; 2560 * 1440	
Image Sensor	CMOS	
Light Source	LED + LED	
Processor	32-bit ARM MCU + DSP	
Image Size	Code 39, 35mm /	
Resolution	400	
Image Size	1/5	
Image Size		
Image Size		
Image Size	LED	
Image Size	20	
Image Size	ABS + PC	
Image Size	5V ± 5%	
Image Size	375mW; 226mW; 750mW	
Image Size	145.0g ± 5g	
Image Size	164.5 * 91.5 * 68.0 mm	
Image Size	+	
Image Size	1D	25 - 25 - 25
		39 - 39 - ASCII 32
		93 - 93 - ASCII 128
		EAN / GSL / UCC-128 Auto, Codabar, MSI
		EAN / JAN-13, UPC-A, JAN-8, Code11, UPCE0
	2D	MICRO QR, QR, AZTEC, PDF417
Image Size	360°, 30°, 45°	

□□□□	Code39 4.17mil□15□□□□6cm-12cm
	Code128 4.17mil□16□□□□7cm-10cm
	□□□□10.83mil□8 bytes□□5cm-16cm
	□QR 1083mil□8 bytes□□7cm-12cm
□□□□	
IP□□	IP52
□□□□	0□50°C/ 32□122°F
□□□□	0□50°C/ 32□122°F
□□□□	20□□85□□□□□□□□
□□□□	20□□85□□□□□□□□
□□□□	15KV□□
□□□	□1.5m□□□□□□



OCBS-2018





OCBS-2018





OCBS-2018





OCBS-2018





OCBS-2018





OCBS-2018

