

# 1D / □□□□□□

## □□□□OCBS -2019□

□□□

□□	USB; □RS232□□□□□
□□□□	□Linux□□□□□□Windows XP□7□8□10□□□□□
□□□□	□□;□□;□□□□□□□□;□□;□□
□□□	□□CMOS□□□
□□	□□LED□□□□+□□LED□□□□
□□□	32□ARM MCU + DSP
□□□□	Code39□35cm /□
□□□	400□
□□□	1/5□□
□□□□	□□□□□□□□□□□□
□□□□	□□□□□□□□LED□
□□□□□	20□
□□□□	□□5V±5□
□□□□	375mW□□□□□; 226mW□□□□□; 750mW□□□□□
	[□□□□□]
□□	289□±5□
□□ □□	□*□*□□180 * 115 * 85 □□□□□□□□
□□□□□	60 * 45 * 38.5□□50□/□□□□□□ = 14.45kg□□□□ = 16.15kg
□□□□	□□
	□□25-□□□□25-□□□□25-□□ Code39-□□Code39-FullASCII Code32 Code93-□□Code93-FullASCII Code128 EAN / GSL / UCC-128□□Codabar MSI EAN / JAN-13 UPC-A JAN-8□□11 UPCE0
	2D MICRO QR□□□□□QR □□□□PDF417
□□□□	□□360°□□□30°□□□45°
□□□□	0□50°C / 32□122°F
□□□□	20□□85□□□□□□□□



OCBS-2019





OCBS-2019





OCBS-2019



