

□□□□□□□□□□□□□□□□

□□□□ OCBS-2089)

□□□



□□□□□□□□

1MP□□□1MP(1280*800);

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□

4□□□□□□□□□□

□□□□□□□□□□

□□□

□□	
□□	OCBS-2089
□□	□□
□□	ABSPC
□□	□□□□□□□□<280mA □□□□□□□□< 130 mA

電流	5 mA (-10%)/500mA
電圧	1.2V
インターフェース	RS-232C、USB HID、USB、POS
表示	LED
メモリ	
撮像素子	CMOS 1280*800
照明	LED
厚さ	4mil
耐電圧	8KV
耐電圧	15KV
耐電圧	1.2m
耐電圧	≥20%
規格	GS1 DataBar™、2D、GS1 DataBar Expanded Stacked、GS1 DataBar、GS1、PDF417
寸法	3.34mil 39 60mm—160mm 3.34mil EAN-13 90mm—150mm 5mil 39 70mm—240mm 5mil EAN-13 70mm—230mm 13mil UPC-A 40mm—450mm 5mil PDF417 65mm—210mm 5mil QR 75mm—140mm 10mil QR 45mm—290mm 10mil DM 30mm—260mm 20mil QR 20mm—480mm
角度	0-360° ±60°
重量	160g
寸法	183*67*90mm
寸法	195*118*82mm/0.42mm
寸法	135*235*410mm
温度	0~45°C
湿度	10%~80%
温度	-20~60°C
湿度	10%~90%













