

**OCBS -C006 32 USB 1D CCD**

□□

2500 CCD  
 280  
 3mil  
 /  
 3cm

□□

□□□□	□□□□	32 ARM
□□□□	□□□□	2500 CCD
	□□	LED 660nm±10nm
	□□□□	280
	□□□□	55° ±25° ±75°
	□□□□	60 25mil 40cm 15mil 32cm 10mil 22cm 5mil 11cm 3mil 3cm
	□□□□	≤110mm
	□□□□	≥0.1 4mil
	□□□□□	15
	□□□□	Code 39 Full ASCII Code 39 Code 32 Code 128 Code 93 Code 11 Codabar / NW7 UPC / EAN / JAN EAN-13 EAN-8 UPC-A UPC-E EAN-128 Interleave 2 of 5 STD 2 of 5 Industrial 2 of 5 , WPC 2 of 5 Pos IATA MSI / PLESSY 2/5 BC-412 UPC-A UPC-E Code 128 Code 93 Coda bar IATA MSI / PLESSY Code 32 STD
	□□□□	□□
□□		100~110mA
□□		30~40mA
□□□□	□□□□	170 L × 60 × 95 H
	□□	185
	□□	ABS
	□□	USB
□□□□	□□□□	-200°C ~ 50 °C
	□□□□	-40°C ~ 70 °C
	□□	0~98
	□□	0~70,000
□□ □□□□	5mil UPC	40 - 160
	10mil Code93	20mm - 240mm
	15mil EAN13	40 - 250
	20mil code128	40 - 380
	40mil code128	80mm -520mm