

4 Android 6.0

OCBS -D4000

Android 6.0

1GRAM 8G ROM TF 64 GB;

28nm ARM Qual-core A53, 1.3-1.5GHz

4G LTE 3G WCDMA

GPS A-GPS

500 LED

SIM PSAM Micro SD TF

3.7V 4000mAh;

4.0 QVGA

IP65

1.5m 6

| | |
|-----|--|
| | |
| | 157x 76x 28 |
| 324 | 324 |
| | 4.0 QVGA TFT-LCD 650000 480 * 800 QVGA LED |
| | SIM Micro SD TF |
| | USB2.0 |
| | |
| | 3.7V 4000mAh |
| | |
| | 28nm ARM Qual-core A53, 1.3-1.5GHz |
| | 1G |
| ROM | 8G NAND Micro SD / TF 64G |
| | |
| | IEEE802.11b / g / n |
| LTE | FDD-B1 B3 B7 B8 B28 TDD-B38 B39 B40 B41 |

| | |
|-------------|---|
| WCDMA / GSM | WCDMA 850MHz; 824MHz-849MHz; 869MHz-894MHz 900MHz; 880MHz-915MHz; 925MHz-960MHz 1800MHz; 1710MHz-1785MHz; 1805MHz-1880MHz 1900MHz; 1850MHz-1910MHz; 1930MHz-1990MHz |
| | 2.0 + EDR / 3.0 + HS / 4.1 + HS 5-10m |
| | |
| | -10 50 |
| | -25 70 |
| | 0 RH--95 RH |
| | 1.5m 6 |
| | 1000 / 0.5m 6 |
| | IP65 |
| | |
| | Android 6.0 |
| | |
| | |
| | |
| | |
| | Mingde966 Symbol 955 N4313 |
| | 4Mil |
| | 1000ft.candles 107640 lux |
| | 104 ± 12 / sec |
| | 47 ± 35 / 35 ± 3 |
| | UPC / EAN Code128 Code39 Code93 Code11 2 5 2 5 2 5 Codabar MSI RSS |
| | |
| | N3680 2D 2D |
| | 752 × 480 |
| | 9000 / 96900 lux |
| VLD | 655 ± 10 |
| | PDF417 MicroPDF417 Com pos ite RSS TLC-39 Datamatrix QR Micro QR Aztec MaxiCode; Pos tal Pos tNet Pos tal Pos tal Pos tal Pos tal KIX 3 |
| | |
| | 13.56MHz; ISO14443A |
| | 500 LED |
| | A-GPS |