

Android

M / N OCBS-D7000

□□

- | Android 4.4.2
- | 1GB RAM □ 8GB ROM
- | 4.0 □ 480 * 800 WVGA IPS □□
- | 1D / 2D □□□□□□□□
- | RFID LF / HF / UHF / □□□
- | □□□□□□□□
- | □□ 3G / Wifi / GPS / □□
- | □□□□□ 5 MP □□ LED □□□□□□□□
- | □□□□□□□□□ 3.7V □ 5200mAh □□
- | □□ IP65 / 1.5 m □□□□

□□

□□□□

- 158mm □ H □ × 75mm □ W □ × 28mm □ D □ ± 2mm
- 300g □□□□□□□□□□
- 4.0 □□ TFT-LCD □ WVGA 480x800 □□□□□□□□
- LED □□
- 3 □ TP □□ 17 □□□□□□ 4 □□□
- 2 PSAM □ 1 SIM □ 1 TF
- □□□□□□□□□ 3.7V □ 5200mAh

□□□□

□□□□□

□□□□

□□

- Cortex A7 1.2GHz □□
- Android 4.4.2
- 1GB RAM □ 8GB ROM □ MicroSD □□□ 32GB □□□

□□□□

□□□□

□□□□□

□□

□□□□

□□

ESD

- 20°C □ 50°C
- 20°C □ 70°C
- 5 □ RH □ 95 □ RH □□□□□
- 5 □□ / 1.5 □ □□
- IP65 □ IEC □□□
- ±15kv □□□□□ ±8kv □□□□□ ±8kv □□ □□

□□□□

SDK

□□

□□

- HHW □□□□□□
- Java
- Android Studio □ Eclipse

□□□□

WWAN

WLAN

WPAN

- WCDMA □ 850/1900 / 2100MHz □□ GSM / GPRS / Edge 850/900/1800 / 1900MHz □
- IEEE 802.11b / g / n
- v2.1 + EDR □□□ v3.0 + HS □□□ v4.0

GPS

GPS A-GPS 5 m

1D

1D N431x

2D CMOS

2D CMOS N6603

RFID

PDF417

MicroPDF417 Composite RSS TLC-39 Datamatrix QR Micro QR MaxiCode

RFID LF

5.0

RFID HF

LED

RFID

RFID LF

125KHz / 134.2KHz FDX-B / HDX

RFID HF

ISO 11784 11785

R / W 2cm 10cm

13.56MHz

ISO 14443A & 15693

R / W 2cm 8cm

PSAM

ISO 7816

PSAM

9600 19200 38400 43000 56000 57600 115200

PSAM

2

PSAM

PSAM

1x

PSAM

1xL

1xDC

1xUSB

PSAM



www.ocominc.com

